



Topaz™ SignatureGem Tablet Installation and Operation with Secure Perfect

Contents

- Overview
- Installation of Topaz SignatureGem LCD Model T-L462-HSB Software
- Installation of Topaz 1X5 Tablet Wintab Driver v2.15
- Operation
- Removal of Software
- Technical Support

Overview

NOTE



DO NOT connect the tablet to your computer before installing Topaz Signature Capture software and Topaz 1x5 Signature Capture Tablet driver.

This document details procedures to install and operate the Topaz Signature Capture Tablet.

- The Signature Capture Software is compatible with Microsoft Windows™ 95, 98, NT, 2000, and XP.
- The Wintab 1X5 Driver works with all Microsoft Windows 32-bit operating systems, including Windows™ 95, 98, Me, NT, 2000, and XP. The Wintab 1X5 driver is also compatible with Citrix. Sixteen-bit application support is provided with the `wintab.dll` which is installed into the Windows system directory. This software allows compatible use of the Signature Tablet with any third-party software.

NOTE



This driver does not use a COM port, so the COM port is available for other serial devices.

Installation of Topaz SignatureGem LCD Model T-L462-HSB Software

➤ To install the Topaz Signature Capture system software:

1. Exit all Windows programs.
2. Insert the Topaz Signature Capture Software System diskette into your disk drive.

Result: In Explorer, navigate to the `sigplus.exe` file on the diskette and double-click to begin the installation.

-
3. During installation, provide the appropriate answers to prompts as they display. Select the model **SignatureGem LCD Model: T-L462-HSB**.

NOTE



You can re-install the `sigplus.exe` software at any time and select alternative installation options.

4. Click **Finish** to exit this installation.

Installation of Topaz 1X5 Tablet Wintab Driver v 2.15

► To install the Wintab 1X5 Driver:

1. If your system currently has another Topaz or other signature tablet Wintab driver installed, it must be uninstalled/removed before installation of the Topaz 1X5 Signature Tablet Driver.
2. Exit all Windows programs.
3. Insert the Topaz Wintab 1X5 Driver CD-ROM into the CD drive.
Result: In Explorer, navigate to the **Wintab15.exe** file on the CD-ROM and double-click to begin the installation.
4. During installation, provide the appropriate answers to prompts as they display. Select HSB as the connection type.
5. Click **Finish** to exit this installation.

Operation

1. Connect the Topaz 1X5 Signature Tablet USB cable to the USB port of your computer and connect the power cord to a power source.
2. Log in to Secure Perfect. From the Secure Perfect, **Personnel** menu, select **Person** to display the **Person Form**.
3. Select the **Photo** tab, then click **Search** to display a current list of records.
4. Select a person record from the records list, then click **Capture Image/Signature**.
Result: The **Secure Perfect Image Capture Application** screen displays.
5. Using the mouse, point to the signature block and right click.
Result: A context menu displays.
6. From the context menu, choose **Select Input Device** from the context menu.
Result: A **Select Profile** screen displays, listing the available input devices on your computer. By default, the input device loads from a file.

-
7. Select the input device you will be using to capture the signature image and click **OK**. (The next time you capture a photo, the program defaults to the input device you select at this time.)
 8. Click **Capture Signature**.
 9. A **Capture Signature** window displays. With the signature wand, have the person associated with this **Person** record sign on the Topaz SignatureGem Pad.
 10. If the signature displayed on your computer screen is acceptable, with your mouse, click **OK** on the **Capture Signature** window.

Result: The **Image Enhancement** window displays, allowing you to crop, resize, or enhance the appearance of the signature.
 11. When you are ready to accept the signature image, click **OK** to return to the **Image Capture Application** window.
 12. When you are returned to the **Image Capture Application** window, select **OK**.

Result: The signature image capture and storage is complete and ready for imprinting on a badge design of your choice. Refer to the Secure Perfect Help system or Administrator's Guide for additional details of the badge production process.

Removal of Software

➤ To remove the Signature Capture Software:

1. Click **Start, Settings, Control Panel**, then **Add/Remove Programs**.
2. Select **Topaz e-Signatures SigPlus 3.40** from the list of installed programs.
3. Click **Change/Remove**.
4. When the removal process is finished, exit the Control Panel.

➤ To remove the Topaz 1X5 Signature Tablet driver software:

1. Click **Start, Settings, Control Panel**, then **Add/Remove Programs**.
2. Select **Topaz 1X5 Tablet Wintab Driver c2.15** from the list of installed programs.
3. Click **Change/Remove**.
4. When the removal process is finished, exit the Control Panel.

Technical Support

Contact the following for technical support:

- Call Topaz Systems, Inc. at (805) 520-8282.
- E-mail support@topazsystems.com or www.topazsystems.com.